

## Aquaterra biosourced knife - Single plain blade - Green

Part #10131



### Description

If you love nature and outdoor sports, this knife is for you! At Wichard we don't simply pay lip service to environment protection. When manufacturing our knives, we do everything practical to contribute to protecting nature on a daily basis. Wichard has gone one step further with our bio-sourced knife, replacing standard materials such as polyamide and polypropylene with naturally occurring products. For this model, we've selected:  
A resin made from castor oil  
Ground sea shells to improve the handle mechanical resistance

**MAIN BENEFIT:** This approach to design and production has cut the carbon footprint for this new Aquaterra knife by 35% in relation to the old range of Wichard

#### BENEFITS:

- Stainless steel plain blade
- High cutting power
- High corrosion resistance
- Safety locking blade
- Light and compact
- Soft grip for better handling
- Colour: sandy brown
- Designed and manufactured in France

#### TECHNICAL FEATURES:

- Blade thickness: 2 mm - 5/64"
- Overall blade length: 8 cm - 3 5/32
- Overall knife length: 195 mm - 7 19/32 / 115 mm - 4 12/32
- Stainless steel grade: MA5
- Material handle: resin of castor oil - ground sea shells

### Applications

Outdoor sports: fishing, hunting etc...  
Outdoor hobbies

## Technical information

**Materials** Handle: resin from castor oil + powdered oyster shell  
- Blade: MA5 stainless steel grade

**Colour** Green

**Weight (g)** 63

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

### Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.

The safety factor is 5 times the breaking load.

WLL = Breaking load / 5

